b~wbridge

Anti-Virus for SAP Solutions

v 3.1

Installation and Configuration Guide



Table of contents

bowbridge Anti-Virus for SAP solutions	3
Product Overview	3
Content filter overview	4
Installation on UNIX/Linux	5
Installation on Microsoft Windows Server	6
Silent and unattended installation	8
SAP-side configuration	9
Understanding the SAP NetWeaver Virus Scan Service	9
Configuring Content Scanning in an ABAP environment	10
- Defining Scanner Groups	10
- Defining Virus Scan Providers	13
- Defining Virus Scan Profiles	16
Advanced Content Scanning - ABAP	20
File extension blacklist	20
File extension whitelist	21
MIME-type blacklist	22
MIME-type whitelist	23
Content validation	24
Blocking active content	25
Logging content scan activity	26

Implementing Content Scanning in the Java Environment	t27
Defining a Scanner Group	27
Defining a Virus Scan Provider (Adapter)	29
Defining Virus Scan Profiles	31
Advanced Content Scanning - Java Configuration	33
File extension blacklist	33
File extension whitelist	34
MIME-type blacklist	35
MIME-type whitelist	36
Content validation	37
Blocking active content	38
Logging Scan Activity	39
Configuring ICAP-based virus scanning	40
Configuring ClamAV-based virus scanning	42
Preloading configuration parameters from configuration fi	les 43
Controling automatic updates	44
Integration with McAfee ePO	45
Integration with OS-level anti-virus updates	48
McAfee Virus Scan Enterprise (Windows)	48
McAfee Endpoint Security (Linux)	48
Parameter reference	50

Product Overview

bowbridge Anti-Virus is an integrated content security solution for SAP®-based applications. NetWeaver application servers. The product secures file transfers from or into SAP applications, leveraging advanced content filters and built-in or external virus scan products from leading vendors.

bowbridge Anti-Virus utilizes SAP's NetWeaver Virus Scan Interface (NW-VSI) to seamlessly and easily enable content scannin.

In addition to virus scanning, bowbridge Anti-Virus supports filtering by file extensions and true content-based MIME-type filters. It further detects and blocks various types of active content and malformed or maliciously embedded files.

bowbridge Anti-Virus offers flexibility and choice when it comes to virus scanning by integrating two industry leading virus scan engines from McAfee and SOPHOS and by providing an industry-standard ICAP-interface, permitting the use of external virus scanners from virtually any security vendor offering and ICAP interface. Lastly, the integration with opensource virus scanner ClamAV allows for cost-effective integration of content scanning functionality.

bowbridge Anti-Virus integrates seamlessly into the SAP management infrastructure. For standard operation, it does not require any operating system level configuration, but is fully customizable from within the SAP management and customization infrastructure.



Content filter overview

Each object passed to Anti-Virus is examined through a series of content filters, controlled by parameters set either at the SAP-system level or in individual application content scanning policies.





Installation on UNIX/Linux

The installation process is virtually identical on all UNIX/Linux platforms, however the screen output on your machine may differ slightly from the screen-shots provided in this documentation.

bowbridge Anti-Virus for SAP solutions for UNIX/Linux is delivered as a gzip-compressed installation shell-script which self-extracts the binaries to be installed. Please copy the file to a location where the current user has write privileges. Extract the file with: gunzip ./install-bowbridge-[version]_[build]_[platform].sh.gz

Executing the resulting installer script with

./install-bowbridge-[version]_[build]_[platform].sh
will start the installation process:



The installer is a menu-driven, interactive application guiding you through the installation process during which you will be required to provide the following information:

- ∽ Agree to the bowbridge Software End User License Agreement
- the SIDadm user ID (when installing as root)
- the installation target directory
- a license to be installed (optional)

Anti-Virus for SAP solutions

Installation and Configuration Guide

Interactive Installation on Windows Server

The Windows version of bowbridge Anti-Virus comes as a single file installer. Local Administrator privileges are required to perform the installation. Please download and execute the file install_bowbridge[version_[build_]Windows86_64.exe and follow the instructions of the installer.



During the installation process, you may deselect components that are not needed in your environment, i.e. one or both of the embedded scan engines, should you not require them.





Providing a license during the installation process is optional, as licenses may be added or replaced at any time after the installation.

After specifying the parameters, the installer copies the product to the installation path provided in the installer.

The entire installation process takes only few minutes to complete.

bowbridge Anti-Virus 3.1 Setup	_ 🗆 X
Installation Complete Setup was completed successfully.	(
Completed	
Show details	
Nullsoft Install System v2.46	
< Back Next >	Cancel

Anti-Virus for SAP solutions

Installation and Configuration Guide

Silent/Unattanded Installation

For automated or unattended rollout, bowbridge Anti-Virus may be installed without user/administrator interaction.

If an installation already exists in the target directory, an upgrade will be performed. Binaries will be updated but configuration files will not be changed or added. Please note the VSA must be stopped for the upgrade to succeed.

On Windows Server:

install_bowbridge[version_[build_]Windows86_64.exe /S /LICENSE=<path
to license file> /D=<non-standard installation directory>

In Silent-Mode the /D parameter MUST be the last parameter of the command line. The installation directory value MUST NOT contain any quotations.

Example:

```
install_bowbridge_318_B435_Windows86_64.exe /S /LICENSE="C:\Users\
bbradm\Desktop\bowbridge-license.lic /D=C:\Program Files\bowbridge3x
```

On Linux/UNIX:

Extract the installer-script from the tar.gz file as described on page 5. run the installer script with the following command-line options:

as SIDadm

--silent --targetdir=<installation directory> --licensefile=<path to the license file>

as root

--silent --targetdir=<installation directory> --licensefile=<path to the license file> --user=<SIDadm user> --group=<SAP-System group>

Example:

```
/:install-bowbridge-318_435_Linux_x86-64.sh --silent --targetdir=/usr/
sap/BBR/bowbridge --licensefile=/home/bbradm/Bowbridge-License.lic
--user=bbradm --group=sapsys
```

SAP-side configuration

For details on how to configure your SAP landscape to enable Virus Protection for your application, bowbridge recommends referring to the latest SAP documentation for your product and version.

Understanding the SAP NetWeaver Virus Scan Service

NetWeaver's Virus Scan Service introduces three abstraction layers:

- 1 Virus Scan Provider: describes the access to a virus scanner
 - Virus Scan Adapter: allows direct access to a virus scanner.
 The adapter is loaded as a dynamic library (DLL or lib) and is executed within the address space of the the J2EE or ABAP engine and is therefore the variant offering the highest performance.
 - Virus Scan Server: defines a (logical or physical) server which gets scan-objects via RPC. This variant has a much lower performance and might fail when scanning large files.
- 2 Virus Scan Group: A Virus Scan Group may cover several Virus Scan Providers.
- 3 Virus Scan Profile: allows to consolidate multiple Virus Scan Groups and combine them using logical AND/OR relationships. Thus it is possible to create high-security deployments in which scan objects need to be checked by multiple servers. Also Virus Scan Profiles may be created to allow application-specific scanning configurations.



Configuring Content Scanning in an ABAP Environment

bowbridge Anti-Virus basic configuration is performed entirely from the SAP customization tools. Very few additional options, such as activating debug tracing and alternative update sources or granular deactivaton of active-content types can be configured via configuration files, either at the host-level or the application server instance level.

Setting up virus protection for ABAP based SAP applications requires three major steps:

- 1. Definition of Virus Scan Groups
- 2. Definition of Virus Scan Providers
- 3. Definition and activation of virus scan profiles

Defining Scanner Groups

A scanner group combines multiple virus scanners of the same type. Since you select the Virus Scan Provider using the scanner group when maintaining the virus scan profile, you must assign each Virus Scan Provider to a scanner group.

We recommend setting up multiple scanner groups if you want to maintain multiple scan configurations on your system.



Configuration Steps:

- 1. Open transaction VSCANGROUP
- 2. Switch to Change mode and select "New Entries"
- 3. Specify name and description for the scanner group

FIELD	NOTES
Scanner Group	freely definable name for the group (i.e. BOWBRIDGE)
Group Text	Description of the group

4. Select the group you just created and double-click "Configuration Parameters" in the Dialog structure pane.

Please configure the initialzation parameters reflecting your desired configuration.



FIELD	REQUIRED	NOTES
INITDIRECTORY	Yes	Path to the bowbride installation folder
INITENGINES	Yes	Virus scanning engine to start. Choose from: - SOPHOS (embedded, default) - MCAFEE (embedded) - ICAP (requires INITSERVERS) - CLAMAV (requires INITSERVERS)
INITSERVERS	for ICAP and CLAMAV	Specifies the ICAP service URL(s) or ClamAV Socket or TCP destination Consult section " <i>Configuring ICAP Backends</i> " and "Integrating ClamAV" for details.
INITTEMP_PATH	No	Specifies the temp directory used by Anti-Virus to store synchronization files and repack SAPCAR archives
INITTIMEOUT	No	Specifies the maximum time for the virus scan engines to start

5. Complete the configuration by saving your settings. You will be prompted to create or assign a customization request to transport the changes.

Defining Virus Scan Providers

NetWeaver supports two types of Virus Scan Providers: *Virus Scan Adapters* and *Virus Scan Servers*.

While both options are fully supported with Anti-Virus, bowbridge and SAP both recommend using the Virus Scan Adapter configuration as it is more stable and delivers much better performance and overcomes other limitations of the Virus Scan Server deployment mode.

Those limitations of the Virus Scan Server deployment model are detailed in SAP note 782963.

If you still need to deploy bowbridge Anti-Virus in the Virus Scan Server model, please contact bowbridge technical support for additional documentation on how to implement that configuration.

Configuration Steps:

- 1. Open transaction VSCAN
- 2. Switch to Change mode and add a new entry

♥	💻 🕲 🗖 🧮 🕻 🖞 🏥 🎁 🎁 🎽 🔛 🔊 💭 🚽 💌
Display Vie	w "Virus Scan Provider Definition": Details
🦻 🗟 🖨	
Provider Type	ADAPTER (Virus Scan Adapter)
Provider Name	VSA_BOWBRIDGE
Virus Scan Provide	Start V Stop
VILUS SCALLETOVIGE	
Scanner Group	EOWERIDGE Display
Scanner Group Status	BOWERIDGE Display Active (Application Server)
Scanner Group Status Server	BOWERIDGE Display Active (Application Server)
Scanner Group Status Server Trace Level	BOWERIDGE Display Active (Application Server) Vhcals4hci_S4H_00 Errors Only
Scanner Group Status Server Trace Level Reinit, Interv.	BOWERIDGE Display Active (Application Server) Vhcals4hci_S4H_00 Errors Only 12 Hours Not yet initialized
Scanner Group Status Server Trace Level Reinit, Interv. Adapter Path	BOWERIDGE Display Active (Application Server) vhcals4hci_S4H_00 Errors Only 12 Hours Not yet initialized /usr/sap/S4H/bowbridge/lbAVB31.so

Enter the information relevant to your installation based on the table below:



FIELD	VALUE	NOTES
Provider Type	ADAPTER	Deployment as "Virus Scan Adapter" for maximum stability and performance.
Provider Name	VSA_ <name></name>	Provide a sensible, unique name for the virus scan provider. The prefix "VSA_"
	default:	must be retained. The name must be
	VSA_ <hostname></hostname>	unique per landscape.
Scanner Group	Select the new Virus Scanner Group from the pull-down options.	Ties the initialization parameters defined in the virus scanner group (i.e. which virus scan engine to start) to this virus scan provider
Status	Active	The Virus Scan Provider is started along with the work processes.
Server	<hostname></hostname>	If the system has multiple application servers (AS), this setting specifies on which AS this VSA should be started.
Relnit interval	8-12	Interval in hours after which the Virus Scan Adapter is to be re-initialized automatically
Adapter Path	fully qualitied path to the VSA shared library on the server specified in the "Server" setting.	Filename of the shared library is: - libAVB31.so on UNIX/Linux - BBVSA3-1.DLL on Windows

3. Save the entries. Specify a customizing request, if prompted to do so.

4. Activate the Virus Scan Provider by clicking the "Start" button bowbridge Anti-Virus will now be started with the settings specified during the previous configuration steps.

Once started, the "Adapter Details" and "Engine Details" will provide additional information:

Virus Scan Provider Details - meanings

After starting up, details of the Virus Scan Provider are displayed in transaction VSCAN. They have the meanings layed out below:

Engine Data

Version	Version of the virus scan engine and/or main virus data
Version Text	Version name returned by the scan engine
Date	Date and time of the last update/virus data
Know Viruses	Number of unique viruses detectable by this engine

Adapter Data

Version	Driver Name	Date	Known Viruses
bowbridge Anti-Virus version	"bowbridge VSA", <license id="">, <license date="" expiration=""></license></license>	VSA build date	number of unique viruses detectable by this engine (if reported)

Adapter Data

Manufacturer	bowbridge Software GmbH	
Product Name	Anti-Virus for SAP-solutions, <version build="" number=""></version>	
Version	Product major release version.	

Defining Virus Scan Profiles

Applications use virus scan profiles to run content checks. Virus scan profiles hold the application specific content security parameters to be passed to bowbridge Anti-Virus in order to perform the proper scan operation.

A virus scan profile specifies steps that are to be run during a content scan. A step is either a virus scanner, which is found using the scanner group, or a step specifies, in turn, a virus scan profile, which is then performed as part of the enclosing virus scan profile.

A virus scan is performed under the name of a virus scan profile. The system administrator can use the profile to activate or deactivate the virus scan for each component.

By default, each SAP application that integrates a virus scan provides a virus scan profile. The names of these virus scan profiles is constructed as follows /<Name of the package of the application>/<Name of the function>. Check the virus scan profiles delivered by SAP, and determine for which components you are activating or deactivating the virus scan.

Create your own virus scan profiles in the Y^* and Z^* namespaces.

Display View "Virus .	Scan Profile": Over	view			
9 8 8 8					
alog Structure	Virus Scan Profile				
🗁 Virus Scan Profile	Virus Scan Profile	Active	Default Pr	Profile Text	TT1
▼ Steps	CBGLMP API/WWI GET			GLM Plus: Load Image Files from WWI Server	*
Step Configuration	/CBUI/WWI REPORT GEN		n	EHS: WWI Report Generation	*
MIME Types	/HCM TMC/DOCUMENT U		0	File Upload Using the Method CL HTTP ENTIT	
	/IC CCS MCM/ICI MAIL		n	Virus Scan Profile for Email via Integrated Com	
	/MDG BS FILE UPLOAD				
	/PAOC EIC APPL COMM			Employee Interaction Center	
	/PAOC RCF BL/HTTP U			SAP E-Recruiting: File Upload Using Method IF	
	/PCO1/SVINCOMING			Scanning Incoming Status Management Emails	
	/PLMU/UI_SPC_BAS/NS				
	/SAPC_RUNTIME/APC_W				
	/SAPC_RUNTIME/APC_W				
	/SARC/ARCHIVING_ADK			Virus Protection Using the Archive Developmen	
	/SBCOMS/SMTP_INBOUND			SMTP Inbox Processing	
	/SCET/DP_VS_ENABLED				
	/SCET/GUI_DOWNLOAD				
	/SCET/GUI_UPLOAD			File Upload Using CL_GUI_FRONTEND_SERVICE	
	/SCMS/KPR0_CREATE				
	/SCMS/KPR0_XML_CREA				
	/SIHTTP/HTTP_DOWNLO				
	/SIHTTP/HTTP_UPLOAD			File Upload Using the Method CL_HTTP_ENTIN	*
		▲ ▶		4 F	
		Position		Entry 1 of 33	



Unlike Virus Scanner Groups and Virus Scan Providers, **the configuration of Virus Scan Profiles is not cross-client.** Virus Scan profiles must therefore be maintained in all active clients separately.

Before maintaining Virus Scan Profiles for your application, log-in to your actual application client.

Configuration Steps:

- 1. Open transaction VSCANPROFILE, and, if necessary, switch to change mode. The screen View: Change "Virus Scan Profile": Overview appears.
- 2. Choose New Entries.
- 3. Specify the data for the virus scan profile according to the table below

New Entries: Details of Added Entries				
🧐 🗟 🖏 🖪				
Dialog Structure	Scan Profile	Z_BOWERIDGE		
Step Configuratic Profile Configuration MIME Types	Profile Text	Virus Scan Profile to be referenced by all active profiles		
	 ✓ Active ✓ Default Profile 	☑Evaluate Profile Configuration Param.		
	Use Reference			
	Link	All steps successful		

Before saving your profile, select the "Active" and "Default Profile" check-boxes and ensure the "Use Reference" checkbox unchecked. As all pre-defined virus scan profiles reference the default, all applications requesting their active virus scan profile will effectively use this new profile.

FIELD	VALUE	NOTES
Scan Profile	Z_ <name>* or Y_<name></name></name>	Specifies the name of the virus scan profile
Profile text		Explanatory text for the virus scan profile
Active	on/off	Specifies that this virus scan profile is active. The virus scan profile can only be used if this indicator is set. SAP applications can used fixed profile names that are delivered. By default, these profiles are not active, meaning that the application program works without a virus scan. You can activate the virus scan for each application by setting this indicator.
Default Profile	on/off	 Indicator that this virus scan profile is the default profile. You can set this indicator for a maximum of one virus scan profile. This virus scan profile is used in the following cases: If an application requests a virus scanner without specifying a virus scan profile If a virus scan profile is requested for which the Use Reference Profile indicator is set, and the Reference Profile is empty
Use Reference	on/off	The Virus Scan Provider is started along with the work processes.
Reference Profile	The input help provides a list of all of the profiles that have already been defined. If you leave the field empty, the system uses the default profile.	Specifies the name of the reference profile. Since a virus scan profile can use another virus scan profile as a reference profile, you can operate multiple applications using the same virus scan profile. If the Use Reference Profile indicator is set in the virus scan profile, this field spe- cifies the name of the reference profile to be used. Instead of the settings of the current virus scan profile, the settings of the reference profile are then used. This means that several virus scan profiles can use the settings of a shared reference profile, such as the scanner groups to be used.
Relationship	 All steps successful: The virus scan must have performed all steps without errors. At least one step successful: It is sufficient if one step of the virus scan was successfully performed. 	Specifies the type of logical linkage for the steps in the virus scan profile. If multiple steps that are to be performed during the virus scan with a virus scan profile are defined for a profile, you can use this field to control how the overall result of the virus scan is to be evaluated. Using multiple steps allows you to scan documents with scan engines from diffe- rent vendors at the same time. The program interprets a virus scan as error-free only if the scan engine returns the return value Check performed successfully or (in the case of cleanups) Clea- nup performed successfully. All other return values are regarded as unsuccessful virus scans. This also includes situations such as: - The program did not check the document because the file name extension is categorized as non-critical. - The program could not check the document, because the document is a pass- word-protected archive. - The scan engine is obsolete.

4. Double-click on "Steps" and add a reference to the new Virus Scanner Group as a new entry at position 0 in the list:

New Entries: Overview of Added Entries						
🦻 🖪 🖪 🖪						
Dialog Structure Virus Scan Profile Stens	Scan Profile	Z_BOWBRIDGE				
• 🗖 Step Configuratic	Steps					
• 🗖 Profile Configuration	Position	Туре	Sc	anner Group	Virus Scan Profile	1
• 🗖 MIME Types	0	Group	🕶 во	WBRIDGE	þ	-
		R	-		Ĩ	-
		R	•			
		R	-			
		м	•			

FIELD	VALUE	NOTES
Position	<integer value=""></integer>	Specifies the position of the scanner group in the virus scan profile. If a virus scan profile uses multiple scanner groups, place these in the desired sequence by assigning a position number.
Туре	"Group" or "Profile"	Specifies whether a step in the virus scan profile refers to a scanner group or another virus scan profile. If you choose Group, the system uses a Virus Scan Server from this group (or a BAdl implementation) for the virus scan. If you choose Pro- file, the program processes the specified virus scan profile instead of this step. You can define any conditions by combining the steps of the virus scan profile with the linkage type of the steps (AND/OR).
Group	The input help provides a list of all existing scanner groups.	Combines multiple Virus Scan Servers. All of the Virus Scan Servers of a scanner group have the same set of configuration parameters and will therefore use the same scan engine.
Profile	The input help provides a list of all existing profiles.	Specifies the name of a virus scan profile that you can include as a step in the profile that you are currently processing.

5. Save the entries

This completes the basic virus scanning configuration in the ABAP stack.

Advanced Content Scanning - ABAP configuration

As a VSI 2.0-certified solution, bowbridge Anti-Virus offers further content scanning capabilities beyond the scanning for malware. Content can be filtered based on its MIME-type, the file extension, the combination of content and extension and based on active content included in the files. While none of those criteria qualify as malware by definition, they still pose a relevant threat to your SAP application and users. Advanced content filters are configured via Virus Scan Profiles as follows:

File Extension Blacklist:

The file extension blacklist may be used to block files with certain extensions prior to the virus scan.

Configuration Steps:

- 1. Open the virus scan profile for your application (or the one it references) and open the "Step Configuration Parameters" of the Step linked to your virus scan group.
- 2. Add "BLOCKEXTENSIONS" as a new entry.
- 3. Specify the extensions you want to block as a semicolon-separated list: Example: ".exe; .com; .dll"

New Entries: Overview of Added Entries				
🧚 🖶 🖶 🖪				
Dialog Structure Control	Scan Profile Z_BOWBRIDGE Position 0			
🔹 🕒 Profile Configuration	Step Configuration Parameters			
• 🗀 MIME Types	Parameter	Value		
	BLOCKEXTENSIONS	. <mark>.exe; .com; .dll</mark>		

File Extension Whitelist:

The file extension whitelist may be used to allow only files with certain extensions to continue to be processed and scanned. All other files will be blocked.

Configuration Steps:

- 1. Open the virus scan profile for your application (or the one it references) and open the "Step Configuration Parameters" of the Step linked to your virus scan group.
- 2. Add "SCANEXTENSIONS" as a new entry.
- 3. Specify the extensions you want to allow as a semicolon-separated list: Example: ".doc; .pdf; .odt"

New Entries: Overview of Added Entries					
🦻 🖪 🖪 🖪					
Dialog Structure Virus Scan Profile Steps Step Configuratic	Scan Profile Z_BOWBRIDGE Position 0				
🔹 🧀 Profile Configuration	Step Configuration Parameters				
 MIME Types 	Parameter	Value			
	SCANEXTENSIONS	.doc; .pdf; .odt			
		Ī			

MIME-Type Filtering

bowbridge Anti-Virus allows for filtering of content based on their MIME-type. The MIME-type of any given file is determined by analysing the content of the file and therefore offers a more thorough protection than filtering based on the filename extension.

MIME filters may be implemented as Whitelist or Blacklist.

Setting up a MIME-type Whitelist

This is the default behaviour of the MIME filter.

Configuration Steps:

- 1. Open the MIME-Types- section of the Dialogue Structure:
- Add entries for each MIME-type you wish to allow. Any file with a MIME-type not on the list of types provided will be rejected with the message "*MIME-Type not allowed*". Simple wildcards, such as "image/*" are supported.

New Entries: Overview of Added Entries					
🦻 🖥 🖪 🖪					
Dialog Structure Virus Scan Profile Control Stand	Scan Profile Z_BOWBRIDGE				
Steps Step Configuration	MIME Types MIME-Type				
	application/pdf				
	application/ms-word image/*				

Setting up a MIME-type Blacklist

Inverting the MIME-type list

Configuration Steps:

- 1. Create a list of entries of MIME-types you want to block, analogous to creating a MIME-type Whitelist.
- 2. Open the "Profile Configuration Parameters" from the Dialogue Structure Pane
- 3. Add the Parameter CUST_MIME_TYPES_ARE_BLACKLIST and set the value to 1. Files with MIME-types defined on the list of MIME-types will be blocked with the message "*MIME-type forbidden*".

New Entries: Overview of Added Entries					
🦻 🖶 🖷 🗣					
Dialog Structure Virus Scan Profile	Scan Profile	Z_BOWBRIDGE			
 Steps Step Configuratic 	Profile Configurati	on Parameters			
Profile Configuration			Value		
• Mume Types		ES_ARE_BLACKLIST	ци 		

Content Validation

Attackers may try to circumvent security by assigning files a file extension that does not match its actual content. bowbridge Anti-Virus can analyze the content of any file and compare the file extension to legitimate extensions for that content type. Deviations are blocked.

Configuration Steps:

- 1. Open the "Profile Configuration Parameters" from the Dialogue Structure Pane
- 2. Add the Parameter CUST_CHECK_MIME and set the value to 1. Files with extensions not matching the well-known extensions for the actual cont
 - ent of the file are blocked with the message "*MIME validation failed*". The mappings of extensions to MIME-types can be adjusted in the file mime_ext_ map, located in your bowbridge installation directory. Re-initializing the Virus Scan Provider is required for the changes to the mime_ext_map file to go into effect.

New Entries: Overview of Added Entries					

Blocking Active Content

Attackers may try upload files with active elements into your application in order to compromise clients accessing these documents or in order to stage a Cross-Site Scripting (XSS) attach.

bowbridge Anti-Virus can detect and block files containing active content. It is equipped with filters detecting:

- JavaScript in HTML, XML and SVG
- Scripts and Macros in Office documents
- JavaScript, OpenAction and ActiveAction in PDF
- Silverlight
- Flash
- Java archives embedded in image files and Office documents.
- XSLT

- 1. Open the virus scan profile for your application (or the one it references) and open the "Profile Configuration Parameters" of the Step linked to your virus scan group.
- 2. Add "CUST_ACTIVE_CONTENT" as a new entry.
- 3. Set the value to 1

New Entries: Overview of Added Entries					
°≱ E. E. E. E.					
Dialog Structure Virus Scan Profile	Scan Profile Z_BOWBRIDG	E			
Steps Step Configuratic	Profile Configuration Parameters	5			
Profile Configuration MIME Types	CUST_ACTIVE_CONTENT	1			

Logging Scan Activity

bowbridge Anti-Virus supports a simple logging of all scan activities in a plain-text, human readable log file.

Logging of scans may be activated via a specific virus scan profile, or in the one referenced as the default profile.

- 1. Open the Step Configuration Parameters for the relevant Step in the Virus Scan Profile dialogue
- 2. Add the parameter SCANLOGPATH and provide a fully qualified filename as the parameter value. Please ensure the scan log file must be in a location writeable for the <SID>adm user on UNIX or SAPService<SID>-user on Windows
- 3. Save the changes

New Entries: Overview of Added Entries					
🦘 🖪 🖪 🖪 🖪					
Dialog Structure Virus Scan Profile Steps Step Step Configuration	Scan Profile Z_BOWBRIDGE Position 0				
Profile Configuration	Step Configuration Parameters				
• 🦲 MIME Types	Parameter	Value			
	SCANLOGPATH	/home/S4Hadm/logs/SAP-scans.log			

Configuring Content Scanning in a Java Environment

The Virus Scan Provider is the service of the J2EE Engine that makes the tc/sec/vsi/ interface interface available to the SAP applications of the Engine.

The implementation involves three steps:

- 1. Defining a Scanner Group
- 2. Defining a Virus Scan Provider
- 3. Defining and activating a Virus Scan Profile.

Depending on the release of your NetWeaver Application Server, the configuration steps below need to be performed in NetWeaver Administrator. In older releases, analogous configurations need to be performed in the Visual Administrator.

Defining a Virus Scanner Group

Virus Scan Providers with identical configuration are grouped together in a Virus Scanner Group. However, even with only one Virus Scan Provider, a Scanner Group containing just this one element must be created.

Configuration Steps:

1. Log-in to NetWeaver Administrator, access the Configuration tab and select "Virus Scan Provider"





Virus Scan Provider: V	firus Scan Provider	Restore Default View 丨 🔶 B			
Favorites 🖌 Related Links 🖌 Go To 🖌	Support Details				
Save Cancel					
Overview Groups Adapters	Servers Profiles				
Virus Scan Groups					
Add Remove All					
Group Name: * BOWBRIDGE	Continue Cancel				
Name	.≟ Description				
N					

3. Mark the newly created Group as the "Default Scan Group" and save the changes

Note: unlike on an ABAP stack, no INIT parameters are set at the Virus Scanner Group level

Defining a Virus Scan Adapter

Although configuration as Virus Scan Server and Virus Scan Adapter are both supported, bowbridge and SAP strongly recommend using the Adapter mode. In Adapter mode, the VSA loads directly into the SAP kernel, providing increased stability and significantly better performance.

Configuration Steps:

- 1. Open NWA's Virus Scan Provider -> Configuration dialogue
- 2. Select the "Adapter" tab
- 3. Switch to Edit Mode and add a new Virus Scan Adapter
- 4. Define a name for the virus scan adapter. Note the name must start with VSA_

/	Overview Groups Adapters Servers Profiles							
	Virus Scan Adapters							
	Add Remove Remove All Activate Deactivate							
	Adapter Name: VSA_BOWBRIDGE Continue Cancel							
		Status	Name ≞	Description				
	F							
	i No available virus scan adapters to display							

5. In the next step, provide the path to the VSA shared library/DLL (libAVB31.so on UNIX, BBVSA3-1.DLL on Windows), set the Scan Group and re-init interval (optional)

Virus Scan Adapter De	s Scan Adapter Details				
Settings T	Settings Trace Parameters				
Virus Scan Adapte	r Settings				
🗸 Default Scan Prov	ider				
Adapter Name:	VSA_BOWBRIDGE				
Adapter Description:	bowbridge Virus Scan Adapter				
Scan Group: *	BOVV -				
Init Interval (Hours):	8				
Maximum Instances:	20				
VSA Library Path:	ap/J2E/bowbridge/libAVB31.so				



7. Open the Parameters tab and add entries for the parameters per the table below:

FIELD	REQUIRED	NOTES
INITDIRECTORY	Yes	Path to the bowbride installation folder
INITENGINES	Yes	Virus scanning engine to start. Choose from: - SOPHOS (embedded, default) - MCAFEE (embedded) - ICAP (requires INITSERVERS) - CLAMAV (requires INITSERVERS)
INITSERVERS	for ICAP and CLAMAV	Specifies the ICAP service URL(s) or ClamAV Socket or TCP destination Consult section " <i>Configuring ICAP</i> <i>Backends</i> " and "Integrating ClamAV" for details.
INITTEMP_PATH	No	Specifies the temp directory used by Anti-Virus to store synchronization files and repack SAPCAR archives
INITTIMEOUT	No	Specifies the maximum time for the virus scan engines to start

8. Save your settings and activate the Virus Scan Provider

Defining Virus Scan Profiles

Application programs use virus scan profiles to check data for viruses. A virus scan profile contains a list of scanner groups that check a document. You can also use a virus scan profile to assign configuration parameters for the virus scanner. If you check for viruses with this virus scan profile, the virus scanner receives the parameters.

A virus scan profile specifies steps that are to be run during a scan. A step is either a virus scanner, which is found using the scanner group, or a step specifies, in turn, a virus scan profile, which is then performed as part of the enclosing virus scan profile.

A virus scan is performed under the name of a virus scan profile. The system administrator can use the profile to activate or deactivate the virus scan for each component. By default, a virus scan profile is provided for each SAP application that integrates virus scan functionality.

Configuration Steps:

- 1. On the Profiles tab page, create a virus scan profile in change mode by choosing the Add button.
- 2. In the Profile Name field, enter the rest of the name after the predefined prefix, and choose Continue. This adds a new row in the Virus Scan Profiles group box.
- 3. In the Virus Scan Profile Details group box, you have the following options on the Settings tab page:
 - Select the profile to be edited as a reference profile by setting the Default Scan Profile indicator.
 - Use the default profile.
 - In the Reference Profile field, select the <Default Profile>.
 - Use a reference profile

Since a virus scan profile can use another virus scan profile as a reference profile, it is possible to operate multiple applications using the same virus scan profile.

This creates a link to an existing reference profile. To do this, use the input help for the Reference Profile field to select a reference profile.

- Define a new profile
 - Choose Add and enter information according to the following table:



FIELD	NOTES
Profile Name	The name of the new profile is displayed.
Profile Description	Description of the new profile
Reference Profile	This indicator must not be set, since the other input fields would otherwise be hidden.
Step Linkage	Linkage of the steps of this profile:
	<u>All steps successful:</u> AND linkage, with which every step must be successful for the overall result to be successful.
	<u>At least one Step successful:</u> OR linkage, with which only one step needs to be successful for the overall result to be successful.
Profile Steps	Use the input help to select profile steps.

- Specify the profile steps in the Profile Steps group box.

- + Choose Add.
- + Use the input help to specify in the Type field whether a group or another profile is to be used.
- + Use input help to specify the value of the group or profile.
- + Configure the list with the buttons Move up, Move down, and Remove.

Settings Parameters					
Virus Scan Profile Settings					
🔽 Default Scan Pro	file				
Profile Name:	Z_BOWBRIDGE				
Profile Description:	default profile using	bowbridge			
Reference Profile:	-				
Profile Steps					
Add Remove Move Up Move Down Step Linkage: * All steps successful					
Step Type Value					
Group	•	BOWBRIDGE			

+ Complete the installation by saving the entries and activating the profile

Advanced Content Scanning - Java configuration

As a VSI 2.0-certified solution, bowbridge Anti-Virus offers further content scanning capabilities beyond the scanning for malware. Content can be filtered based on its MIME-type, the file extension, the combination of content and extension and based on active content included in the files. While none of those criteria qualify as malware by definition, they still pose a relevant threat to your SAP application and users. Advanced content filters are configured via Virus Scan Profiles as follows:

File Extension Blacklist:

The file extension blacklist may be used to block files with certain extensions prior to the virus scan.

Configuration Steps:

- 1. Open the Parameters tab of the relevant Profile in Edit mode
- 2. Choose Add to create a new entry
- 3. Select BLOCKEXTENSIONS from the input help
- 4. Set the type to CHAR
- 5. Provide the semicolon-separated list of extensions to block:

٧	irus	Scan P	rofile Details			
	/	Settin	gs Parameters			
	Vi	rus Sc	an Profile Parameters			
	4	\dd	Remove Remove All			
		Valid	Name	Туре	Value	
			BLOCKEXTENSIONS	CHAR 💌	.exe; .com; .html	

File Extension Whitelist:

The file extension whitelist may be used to allow only files with certain extensions to continue to be processed and scanned. All other files will be blocked.

Configuration Steps:

- 1. Open the Parameters tab of the relevant Profile in Edit mode
- 2. Choose Add to create a new entry
- 3. Select SCANEXTENSIONS from the input help
- 4. Set the type to CHAR
- 5. Provide the semicolon-separated list of extensions to process:

V	irus	Scan P	Profile Details			
	/	Settin	igs Parameters			
	۷	irus Sc	an Profile Parameters			
		Add	Remove Remove All			
		Valid	Name	Туре	Value	~
			SCANEXTENSIONS	CHAR 👻	.pdf; .doc*; .tif*; .jpg; .gif	

MIME-Type Filtering

bowbridge Anti-Virus allows for filtering of content based on their MIME-type. The MIME-type of any given file is determined by analysing the content of the file and therefore offers a more thorough protection than filtering based on the filename extension.

MIME filters may be implemented as Whitelist or Blacklist.

Setting up a MIME-type Blacklist

Configuration Steps:

- 1. Open the Parameters tab of the relevant Profile in Edit mode
- 2. Choose Add to create a new entry
- 3. Select BLOCKMIMETYPES from the input help
- 4. Set the type to CHAR
- 5. Provide the semicolon-separated list of MIME-types to block:

Virus :	Scan P	rofile Details			
	Settin	gs Parameters			
Vi	rus Sc	an Profile Parameters			
A	\dd	Remove Remove All			
	Valid	Name	Туре	Value	
		BLOCKMIMETYPES	CHAR	image/gif; application/ms-word	

Setting up a MIME-type Whitelist

Configuration Steps:

- 1. Open the Parameters tab of the relevant Profile in Edit mode
- 2. Choose Add to create a new entry
- 3. Select SCANMIMETYPES from the input help
- 4. Set the type to CHAR
- 5. Provide the semicolon-separated list of MIME-types to process:

Virus Scan I	Profile Details			
Settir	ngs Parameters			
Virus So	an Profile Parameters			
Add	Remove Remove All			
Valid	Name	Туре	Value	
	SCANMIMETYPES	CHAR	application/pdf; image/*	

Content Validation

Attackers may try to circumvent security by assigning files a file extension that does not match its actual content. bowbridge Anti-Virus can analyze the content of any file and compare the file extension to legitimate extensions for that content type. Deviations are blocked.

- 1. Open the Parameters tab of the relevant Profile in Edit mode
- 2. Choose Add to create a new entry
- 3. Select CUST_CHECK_MIME from the input help
- 4. Set the type to BOOL and value to 1
- 5. Save the entries

Virus Scan P	Profile Details			
Settin	gs Parameters			
Virus Sc	an Profile Parameters			
Add	Remove Remove All			
Valid	Name	Туре	Value	
	CUST_CHECK_MIME_TYPE	BOOL	1	

Blocking Active Content

Attackers may try upload files with active elements into your application in order to compromise clients accessing these documents or in order to stage a Cross-Site Scripting (XSS) attach.

bowbridge Anti-Virus can detect and block files containing active content. It is equipped with filters detecting:

- JavaScript in HTML, XML and SVG
- Scripts and Macros in Office documents
- JavaScript, OpenAction and ActiveAction in PDF
- Silverlight
- Flash
- Java archives embedded in image files and Office documents.
- XSLT

- 1. Open the Parameters tab of the relevant Profile in Edit mode
- 2. Choose Add to create a new entry
- 3. Select CUST_ACTIVE_CONTENT from the input help
- 4. Set the type to BOOL and value to 1
- 5. Save the entries

Virus Scan F	Profile Details			Ξ
Settir	gs Parameters			
Virue Sr	an Drofile Darametere			
Add	Remove Remove All			
Valid	Name	Туре	Value	
	CUST_ACTIVE_CONTENT	BOOL	1	

Logging Scan Activity

bowbridge Anti-Virus supports a simple logging of all scan activities in a plain-text, human readable log file.

Logging of scans may be activated via a specific virus scan profile, or in the one referenced as the default profile.

- 1. Open the Parameters tab of the relevant Profile in Edit mode
- 2. Choose Add to create a new entry
- 3. Select SCANLOGPATH from the input help
- 4. Set the type to CHAR and
- 5. Provide a filename in a location writable by <SID>adm on UNIX and SAPService<-SID> on Windows
- 6. Save the entries

1	'irus	Scan F	Profile Details			
	/	Settin	gs Parameters			
	Vi	rus Sc \dd	an Profile Parameters Remove Remove All			
		Valid	Name	Туре	Value	
			SCANLOGPATH	CHAR	/home/j2eadm/logs/scan.log	

Configuring ICAP-based virus scanning

bowbridge Anti-Virus can leverage existing ICAP-capable virus scan engines. Despite offering less scan performance than the embedded engines, the use of ICAP can be an interesting option if:

- scanning with an engine from a specific vendor, other then McAfee or SOPHOS is desired
- separation of SAP-management and security management is desired.
- ICAP-based virus scanning is provided as a service by your security department
- you do not wish to run a virus scan engine on your NetWeaver application server

To use ICAP for virus scanning, you need to specify "ICAP" as the INITENGINES parameter:

- on ABAP: in the Virus Scan Group configuration

Change View "Confi	iguration Parameters": Ov	erview	
🦻 New Entries 🗈 🖶 🖾			
Dialog Structure	Scanner Group BOWBRIDGE Configuration Parameters		
	Parameter	Value	
	INITDIRECTORY	/usr/sap/S4H/bowbridge	
	INITENGINES	ICAP	-
	INITSERVERS	icap://icap.bowbridge.net/avscan;2000;20000	

- on J2EE: in the Virus Scan Provider parameters tab

Virus S	Virus Scan Adapter Details					
	Settings Trace Parameters					
Vir	Virus Scan Adapter Parameters					
A	dd	Remove All				
	Valid Name Type Value				-	
			CHAR	/usr/sap/J2E/bowbridge		
	CHAR ICAP			ICAP		
	INITSERVERS CHAR icap://icap.bowbridge.net/avscar;2000;20000					

bowbridge Anti-Virus supports up to two ICAP servers. When two ICAP servers are provided, concurrent connections are automatically shared among the two ICAP servers. Also, if one of the ICAP servers fails, the remaining one will be used for scanning. To setup ICAP servers, you need to configure the INITSERVERS parameter to contain the ICAP URL(s) and timeout values in the following format:

Scanning with one ICAP server:

icap://[hostname or IP]:[port - optional]/ICAP-service-path ; connect-timeout ; operation timeout Example: icap://192.168.10.123:11344/avscan;2000;20000

Note: the port option i.e. ":11344" is only required if your ICAP service runs on a port other than the default port TCP/1344)

Scanning with two ICAP servers:

icap://[server 1 hostname or IP]:[port - optional]/ICAP-service-path ; connect-timeout ; operation timeout ; icap://[server 2 hostname or IP]:[port - optional]/ICAP-service-path ; connect-timeout ; operation timeout

Example: icap://192.168.10.123/avscan;2000;20000;icap://192.16.10.124/avscan;3000;25000

ICAP over SSL ("ICAPS")

ICAP over SSL is supported on select platforms (UNIX only). To activate this functionality, specify the ICAP URL starting with "icaps://". The default port for ICAP over SSL is TCP/1345

Example: icaps://192.168.10.123/avscan;2000;20000

Configuring ClamAV-based virus scanning

bowbridge Anti-Virus can leverage the open-source virus scanning solution "ClamAV". While the use of ClamAV is not recommended for production environments, it represents an interesting alternative to commercial virus scanning engines for development instances or as a "second opinion scanner".

Connection to ClamAV's Clam-Daemon (clamd) can be via setup a local socket (UNIX/ Linux only) or via TCP/3310.

To use ClamAV for virus scanning, you need to specify "CLAMAV" as the INITENGINES parameter.

- on ABAP: in the Virus Scan Group configuration

		, DVCIVICW	
0	🕶 🗠 😒 😒 I 📙 » 🔻	16 \$ \$ \$ \$ \$ \$ \$ 0 0 0) 徐 和 台 和 和 🧮 🗖 🥝 💻
Change Vie	ew "Configuration Parameters"	": Overview	ition": Details
🦘 New Entries	- 🗅 🖶 🕫 🖡 🖡 🖟		
Dialog Structure	Scanner Group BOWBRIDGE	1	
Scanner Gro	oups		
Conngui	Configuration Parameters		
	Parameter	Value 📅	
	INITDIRECTORY	/usr/sap/S4H/bowbridge	
	INITENGINES	CLAMAV	
	INITSERVERS	tcp://icap.bowbridge.net:3310	
		·	
		4 >	
	E.	Decition Entry 1 of 2	10.2010 22:11:04
	- + >	Endy 1013	
		SAD	4
		5AV	
		Engine Data	4 / / ·
		Engine Data	
		Engine Data	
		Engine Data Version 0.98 Version Text ClamAV 0.98.4/22382/Mon Oct	17 17:55:52 2016
		Engine Data Version Version Engine CamAV 0.98.4/22382/Mon Oct Date Thu Oct 6 21:11:00 2016	17 17:55:52 2016
		Engine Data Version 0.98 Version Text ClamAV 0.98.4/22382/Mon Oct Date Thu Oct 6 21:11:00 2016 Known Viruses Thu Oct 6 21:11:00 2016	17 17:55:52 2016
		Engine Data Version Text ClamAV 0.98.4/22382/Mon Oct Date Thu Oct 6 21:11:00 2016 Known Viruses	17 17:55:52 2016
		Engine Data Version 0.98 Version Text ClamAV 0.98.4/22382/Mon Oct Date Thu Oct 6 21:11:00 2016 Known Viruses Loaded Drivers	17 17:55:52 2016
		Engine Data Version 0.98 Version Text: ClamAV.0.88.4/22382/Mon.Oct Data Thu Oct 6 21:11:00 2016 Koown Viruses Loaded Drivers Users of Device there	17 17:55:52 2016
		Engine Data Version Text: ClamAV 0.98.4/22382/Mon Oct Date Thu Oct 6 21:11:00 2016 Known Viruses Loaded Drivers Version [Driver Name Version] [Driver Na	17 17:55:52 2016
		Engine Data Version 0.98 Version Text CamAV 0.98.4/22382/Mon Oct Data Thu Oct 6 21:11:00 2016 Krown Viruses Loaded Drivers Version Driver Name 3.1 bowbridge VSA, Uc. 1136, exp. 2016-1	17 17:55:52 2016 Date Known Viruses 2-31] Thu Oct 6 00:00:00 2016
			17 17:55:52 2016 17 17:55:52 2016 2-31 [Thu Oct 6 00:00:00 2016]

- on J2EE: in the Virus Scan Provider parameters tab

/	Settings Trace Parameters						
Vi	Virus Scan Adapter Parameters						
Add Remove All							
	Valid	Name	Туре	Value			
		INITDIRECTORY	CHAR	/usr/sap/J2E/bowbridge			
		INITENGINES	CHAR	CLAMAV			
		INITSERVERS	CHAR	/var/lib/clamav/clamd-socket			

Preloading configuration parameters from configuration files

In some deployments, configuration settings need to be provided to bowbridge Anti-Virus without them being configured at the SAP customization level. For this purpose, Anti-Virus will check for the presence of a host-global configuration file and a SID-specific configuration file.

Further, some functionality, such as trace-file output, alternate update sources and the definition of what is detected as active content can be set via configuration files only.

Host-global configuration file

The host-global configuration file (UNIX only) is to be created and stored as: /etc/bowbridge/bbvsa31.cfg

SID-specific configuration file

The SID-specific configuration file is to be created and stored as: /usr/sap/[SID]/ bowbridge/bbvsa31.cfg

Anti-Virus evaluates parameters in the following order:

- host-global configuration file
- SID-specific configuration file
- parameters passed from the SAP application server

Configuration file parameter format

The host-global and SID-specific configuration file follow the same simple format. It is

- structured in sections:
 - INIT
 - SCAN
 - ACTIVE_CONTENT
 - TRACE
 - UPDATE
 - SCRIPTS
 - EPO
 - MISC
 - •

where section names need to be in brackets (i.e. $\ensuremath{\mathsf{[INIT]}}$).

Values for the supported parameters are provide without quotation marks after an equal sign (i-e: INITENGINES=SOPHOS;2)

Name-Value-pairs or entire sections may be commented out with a preceeding "#"

Controling Automatic Updates

bowbridge Anti-Virus, when used with either of the integrated virus scanning engines, performs automatic downloads of virus scanning engine updates and virus definition updates from the bowbridge CDN.

These updates are installed autmatically. Manual intervention or scheduled re-initialization of the Virus Scan Adapter is not required.

Update Sources

By default, bowbridge Anti-Virus attempts to download updates directly from the bowbtridge CDN via HTTP/HTTPS. The URLs accessed are http://update.update.bowbridge.net and http(s)://cdn.update.bowbridge.net

It is in the nature of a CDN that IP-addresses for the CDN edge node can (and will) change over time and based on your location.

bowbridge Anti-Virus can be configured to download updates via a Web-Proxy or from an internal update source, such as the bowbridge Local Update Service. Please refer to the Configuration Parameter Overview at the end of this document for details or contact bowbridge technical support for assistance on how to configure alternate update sources.

Integration with McAfee ePO

bowbridge Anti-Virus provides an integration with McAfee e-Policy Orchestrator (ePO). Once enabled, McAfee customers are able so monitor security relevant events and product properties in ePO. To benefit from the integration, it is required to install and configure the McAfee Agent on the SAP systems and establish communication between the McAfee agent and the ePO server.

SAP-server-side configuration (Linux/UNIX only)

In order to activate the integration on UNIX platforms an additional installation step is required:

- Please open a terminal and login as root or su to root
- Change into your bowbridge installation directory
- Execute the script "enable_ePO_integration.sh". It will automatically unpack and install the additional files and activate the integration
- restart the Virus Scan Adapter in order to activate the changes

ePO-side configuration

In order for ePO to interpret the events generated by Anti-Virus, it is necessary to install the bowbridge ePO extension.

To do so, navigate to the Extensions settings from the ePO management interface:





Click the "Install Extension"-Button at the bottom of the page and select the bowbridge ePO Extension file:

Software Extensions			
Install Extension			
Name:	S_BBRSAP3000		
Version:	1.0.0.0		
Product:	BowBridge		
Details:	Extension for S_BBRSAP3000		
Signed by:	Not signed by McAfee		
Requires:	• core • EPOCore		

Choose OK to activate the extension.

Extensions					
tensions					
McAfee	Name: Version:	S_BBRSAP3000	Status: Requires:	Installed	Modules
Policy Orchestrator Help Content	Installed by:	admin - April 6, 2014 3:19:42 PM PDT		Core Modules 2.5 ePO Core 4.5	
1cAfee Agent			Details:	Extension for S_BBRSAP3000	
Product Improvement Program					
Shared Components					

bowbridge Anti-Virus properties will be displayed and updated in your ePO console:

System Properties	Products	Threat Events	McAfee Age	t		
Product			Version		Dat Version	
Agent BowBridge AntiVirus	Bridge for SAP	solutions	4.8.0.887 3.0.11		7400.0	
Product properties	for BowBrid	ge AntiVirus Bri	dge for SAP s	lutions		
BowBridge AntiVin	us Bridge for	SAP solutions	S_B	S_BBRSAP		
Product Version			3.0.	1		
Language			Eng	sh (Unite	d States)	
Hotfix/Patch Versi	on		147			
Engine Version			560	.1067		
DAT Version			740	7400.0		
Details						
DAT File 1			/usr	sap/NPL/	bowbridge/mcafee/1396819810/dat/avvnames.dat	
DAT File 1 Date			6.4.	6.4.2014		
DAT File 2			/usr	sap/NPL/	bowbridge/mcafee/1396819810/dat/avvscan.dat	
DAT File 2 Date			6.4.	6.4.2014		
DAT File 3			/usr	/usr/sap/NPL/bowbridge/mcafee/1396819810/dat/avvclean.dat		
DAT File 3 Date			6.4.	6.4.2014		
Last update			Sun	Apr 6 23:	30:10 2014	
General						
DatVer			740	.0		
EngineVer			560	.1067		

Event Generated Time	۳	Event ID	Event Category	Threat Name	Action Taken
4/6/14 2:08:45 AM		202958	Update failed	Engine update failed	Automatic engine update
4/6/14 2:08:45 AM		202960	Update failed	Automatic DAT update failed	DAT update not deployed
4/6/14 2:08:19 AM		202950	Service started	VSA started	None
4/6/14 2:07:36 AM		202952	Service ended	VSA shut down	None
4/6/14 2:05:09 AM		202960	Update failed	Automatic DAT update failed	DAT update not deployed
4/6/14 2:03:05 AM		202960	Update failed	Automatic DAT update failed	DAT update not deployed
4/6/14 2:03:05 AM		202950	Service started	VSA started	None
4/6/14 2:03:05 AM		202957	Update ended	Engine update deployed	Engine 5600.1067 deploye
4/6/14 2:03:05 AM		202954	Malware detected	EICAR test file	Blocked
4/6/14 2:03:05 AM		202959	Update ended	DAT update deployed	DAT 7400.0 deployed
4/6/14 2:03:05 AM		202952	Service ended	VSA shut down	None
4/6/14 2:03:05 AM		202950	Service started	VSA started	None
4/6/14 2:03:05 AM		202954	Policy (policy.detect)	MIME type blocked	Blocked
4/6/14 2:03:05 AM		202952	Service ended	VSA shut down	None
4/6/14 2:03:05 AM		202950	Service started	VSA started	None
4/6/14 2:03:05 AM		202956	Scan failed	BowBridge license invalid or expl	Blocked

Security events will be displayed in your ePO console:

Deactivating the ePO integration

In order to deactivate the forwarding of properties and events to ePO, edit your relevant bbvsa30.cfg configuration file and delete or comment-out (by adding "#" in front of the parameter) the EPOLOG=1 parameter in the [EPO]-section of the configuration file.

Integration with OS-level anti-virus updates

bowbridge Anti-Virus can leverage centrally distributed updates to McAfee Virus Scan Enterprise for Windows and McAfee Endpoint Security for Linux.

Configuration on Windows Servers:

Locate and open the configuration file bbvsa31.cfg in a text editor locate the [UPDATE] section and adjust the following parameters: VSE_DATDIR= <Fully qualified path to the directory where AVVSCAN.DAT is located> VSE_ENGINEDIR= <Fully qualified path to the directory where MSCAN64A.DLL is located> VSE EXTRADATDIR=<optional, fully qualified path to where EXTRA.DAT is located>

In default Virus Scan Enterprise installations, the values will be: VSE_DATDIR=C:\Program Files (x86)\Common Files\McAfee\Engine VSE_ENGINEDIR=C:\Program Files (x86)\Common Files\McAfee\Engine\x64 EXTRADATDIR=C:\Program Files (x86)\Common Files\McAfee\Engine

Anti-Virus will monitor these files for modification and trigger copying and applying the updates as soon as a change is detected.

For the changes to become active, please stop/start the VSA, or terminate the UPD-MCAF.EXE process in Task Manager. The process will be restarted automatically and leverage the new configuration.

Configuration on Linux Servers

Locate and open the configuration file bbvsa31.cfg in a text editor locate the [UPDATE] section and adjust the following parameters:

ENS_LIBDIR=<Fully qualified path to the directory where the engine version subdirectories are located>

ENS_DATDIR=<Fully qualified path to the directory where the DAT subdirectories are located>

ENS_EXTRADATDIR=<optional, fully qualified path to where the extra dat is located> ENS_SIDADM=<name of the SIDadm user of the instance> In default Endpoint Security for Linux installations, the values will be: ENS_LIBDIR=/opt/isec/ens/threatprevention/var/engine/lib ENS_DATDIR=/opt/isec/ens/threatprevention/var/engine/dat ENS_EXTRADATDIR=/opt/isec/ens/threatprevention/var/engine/dat/extra

Granting UPDMCAF extended privileges

With Endpoint Security for Linux, McAfee updates are readable for the root-user only. Therefore the UPDMCAF process must have access to root permissions via a SetUID configuration.

When running with SUID root, the process will immediately drop privileges to the SIDadm user configured in the ENS_SIDADM parameter (or SIDadm user name derived from the SAPSYSTEMNAME environment variable).

In order to give the required permissions to the UPDMCAF process, login or su to the root user and perform the following steps inside the bowbridge installation directory:

su root chown root UPDMCAF chmod 755 UPDMCAF chmod +s UPDMCAF exit

For the changes to go into effect, please stop/start the VSA (waiting for the UPDMCAF process to terminate) or simply kill the UPDMCAF process; it will be restarted automatically.

Configuration Parameter Reference

Initialization Parameters

Section Name:	INIT
Parameter Name:	INITDIRECTORY
Parameter Type:	String (pszChar)
Description:	Specifies the path to where AVB is installed. All paths for loading of libraries, components and engines are built based on
	INITDIRECTORY
Default:	n/a
Set via:	SAP Customizing/Configuration files

Section Name:	INIT
Parameter Name:	INITENGINES
Paramter Type:	String (pszChar)
Values:	ICAP, CLAMAV, SOPHOS, MCAFEE, DUMMY
Description:	Specifies the virus scan engine to use. CLAMAV and ICAP also require INITSERVERS to be defined.
	The DUMMY engine allows an adapter to be configured on the system but does not provide any actual scanning
	capabilities.
Default:	SOPHOS
Set via:	SAP Customizing/Configuration files

Section Name:	INIT
Parameter Name:	INITSERVERS
Parameter Type:	String (pszChar)
Description:	For ICAP: ICAP URL(s) to the scan servers. URL format:
	icap:// <ip-adress>[:port]/<service path="">; <connect timeout="">;<scan timeout=""></scan></connect></service></ip-adress>
	For HA and Load-Balancing (Round Robin scheme) 2 ICAP URLs can be specified, separated by semicolon:
	icap:// <lfirst p-adress="">[:port]/<service path="">; <connect timeout="">;<scan timeout="">;icap://<second ip-adress="">[:port]/</second></scan></connect></service></lfirst>
	<service path="">; <connect timeout="">;<scan timeout="">;</scan></connect></service>
	Load-balancing can be switched off by adding ";HA-ONLY" after the second: CAP URL. i.e.:
	icap:// <ifirst p-adress="">[:port]/<service path="">; <connect timeout="">;<scan timeout="">; icap://<second ip-adress="">[:port]/</second></scan></connect></service></ifirst>
	<service path="">; <connect timeout="">;<scan timeout="">;HA-ONLY</scan></connect></service>
	For ClamAV: Filesystem-Path to the ClamAV socket file. For example:
	/var/run/clamav/clamd.sock
	For remote connections:

	tcp:// <ip-address>:<port></port></ip-address>
Default:	n/a
Set via:	SAP Customizing/Configuration files

Section Name:	INIT
Parameter Name:	INITTEMP_PATH
Parameter Type:	String (pszChar)
Description:	Overrides the OS/Environment-provided temp-path.
	Locking and synchronization files will be created and maintained in this directory. Further the repackaging of SAPCAR
	archives is performed in this directory
Default:	n/a
Set via:	SAP Customizing/Configuration files

Section Name:	INIT
Parameter Name:	INITTIMEOUT
Parameter Type:	Integer
Description:	Specifies the number in seconds after which the adapter initialization must be completed
Default:	90
Set via:	SAP Customizing/Configuration files

Section Name:	INIT
Parameter Name:	SAPCARPATH
Parameter Type:	String (pszChar)
Description:	Specifies the fully qualified path to the SAPCAR executable. This parameter is needed only if handling of SAPCAR files
	should be performed by the SAPCAR executable rather than the built-in SAPCAR decompression.
Default:	n/a (commented out)
Set via:	Configuration files

Scan Parameters

Section Name:	SCAN
Parameter Name:	SCANBESTEFFORT
Parameter Type:	Bool
Description:	Toggles whether the scan engine should use ALL available technologies to scan the file (signature, heuristics, none) is left to the scan engine.
Default:	1
Set via:	SAP Customizing Virus Scan Profile/Configuration files
Section Name:	SCAN
Parameter Name:	SCANALLFILES
Parameter Type:	Paal

Parameter Type:	Bool
Description:	Toggles whether the scan engine should scan ALL files or may choose to not scan certain files, that may be considered
	benign (i.e. text/plain)
Default:	1
Set via:	SAP Customizing Virus Scan Profile/Configuration files

Section Name:	SCAN
Parameter Name:	SCANEXTRACT
Parameter Type:	Bool
Description:	Toggles whether the scan engine should unpack and scan inside archives
Default:	TRUE
Set via:	SAP Customizing Virus Scan Profile/Configuration files
Note:	SCANEXTRACT = 0 cannot be used with ICAP

Section Name:	SCAN
Parameter Name:	SCANEXTRACT_DEPTH
Parameter Type:	Integer
Description:	Specifies the maximum number of nested archives that will be unpacked for scanning. Exceeding the value will result in
	SCAN_FAILED
Default:	20
Set via:	SAP Customizing Virus Scan Profile/Configuration files

Section Name: Parameter Name:	SCAN BLOCKACTIVECONTENT (= CUST_ACTIVE_CONTENT)
Description:	Toggles the detection and blocking of active content. Granular configuration of what is considered active content is to be performed in the [ACTIVECONTENT] section of the bbvsa30.cfg configuration file. SAP Customizing does not provide sufficient configuration options.
Default:	0
Set via:	SAP Customizing Virus Scan Profile/Configuration files
Section Name:	SCAN
Parameter Name:	CHECKCONTENT
Parameter Type:	String (pszChar)
Description:	RegEx Filter, Largely irrelevant for file-based scanning
Default:	n/a
Section Name:	SCAN
Parameter Name:	CHECKMIMETYPE (= CUST_CHECK_MIME_TYPE)
Parameter Type:	Bool
Description:	Toggles the MIME-to-Extension check. When TRUE, the detected MIME type and file extensions will be checked against the mime_ext_map file. Mappings not detected in the map file will result in the file being blocked.
Default:	0
Set via:	SAP Customizing Virus Scan Profile/Configuration files
Section Name:	n/a
Parameter Name:	CUST_CLEAN
Parameter Type:	Bool
Description:	Toggles the signal sent to the virus scan engine to attempt to clean infected files. For this parameter to have an effect with ICAP-connected scan engines, the ICAP-sever must be configured on server-side to attempt cleaning of infected files.
Note:	From a forensics perspective, bowbridge does not recommend using cleaning of infected files, as the originally uploaded files will be modified in this process.
Set via:	SAP Customizing Virus Scan Profile (Profile Parameter)

Section Name: Parameter Name: Parameter Type: Description: Note: Set via:	n/a CUST_NO_SCANINFO Bool Requests the VSA to return the respective return-code only and not attach a Scan-Information structure. Hence, the MIME-type, File-extension and blocking reasons are not provided back to the calling function. From a forensics perspective, bowbridge does not recommend using this parameter as it keeps important forensic information from being written to the SAP Security Audit Log. SAP Customizing Virus Scan Profile (Profile Parameter)
Section Name:	SCAN
Parameter Name:	SCANMIMET YPES
Description:	MIME types Whitelist. Semicolon-delimited list of MIME-Types. Wildcards ("*" and "?") are permitted. Only files with MIME-types found on this list will be accepted for further processing. All other files will be blocked with BLOCKED_BY_POLICY ("MIME-Type not allowed")
Default:	n/a
Set via:	SAP Customizing Virus Scan Profile/Configuration files
Section Name: Parameter Name: Parameter Type: Description: Default: Set via:	SCAN BLOCKMIMETYPES String (pszChar) MIME types Blacklist. Semicolon-delimited list of MIME-Types. Wildcards ("*" and "?") are permitted. Files with MIME-types found on this list will not be accepted for further processing. They will be blocked with BLOCKED_BY_POLICY ("MIME-Type forbidden") n/a SAP Customizing Virus Scan Profile/Configuration files
Section Name:	SCAN
Parameter Name:	SCANEXTENSIONS
Parameter Type:	String (pszChar)
Description:	File extension Whitelist. Semicolon-delimited list of MIME-Types. Wildcards ("*" and "?") are permitted. Only files with extensions found on this list will be accepted for further processing. All other files will be blocked with BLOCKED_BY_POLICY ("Extension not allowed")
Default:	n/a
Set via:	SAP Customizing Virus Scan Profile/Configuration files

Section Name: Parameter Name: Parameter Type: Description:	SCAN BLOCKEXTENSIONS String (pszChar) File Extension Blacklist. Semicolon-delimited list of MIME-Types. Wildcards ("*" and "?") are permitted. Files with extensions found on this list will not be accepted for further processing. They will be blocked with BLOCKED_BY_POLICY ("Extension forbidden")		
Set via	SAD Customizing Virus Scop Drofile /Configuration files		
Saction Name:	SC AN		
Developmenter Nerror			
Parameter Name:	ameter Name: SCANLOGPATH		
Parameter Type:	String (pszchar)		
Description:	Fully qualified path to a log file to which all scanning activity will be logged in a hu-		
man readable forn	nat. The containing directory must exist.		
Default:	n/a		
Set via:	SAP Customizing Virus Scan Profile/Configuration files		
Section Name:	SCAN		
Parameter Name:	BLOCKHTMLINPDF		
Parameter Type:	Bool		
Description:	When set, HTML tags in PDF documents are flagged as "Chameleon File", resulting in blocking of the file. Note: As		
	there is an overlap between valid HTML and PDF tags (i.e.), Support recommends to disable it by default,		
	based on a high number of false positives.		
Default:	1		
Set via:	Configuration files		

Active Content Definitions

These parameters define what potentially dangerous content-types are flagged as active content:

Section Name:	ACTIVECONTENT
Parameter Name:	PDF_JAVASCRIPT
Parameter Type:	Integer [0-2]
Description:	Toggles the blocking of Javascript in PDF.
	0: Off
	1: identify <code>"/JS"</code> and <code>"/JavaScript"</code> active content
	2: identify "/JavaScript" active content
Default:	1
Set via:	Configuration files

Section Name:	ACTIVECONTENT
Parameter Name:	PDF_ACTIVE_ACTION
Parameter Type:	Bool
Description:	Identify "/AA" as active content
Default:	1
Set via:	Configuration files

Section Name:	ACTIVECONTENT
Parameter Name:	PDF_OPEN_ACTION
Parameter Type:	Bool
Description:	Identify "/OpenAction" as active content
Default:	1
Set via:	Configuration files

Section Name:	ACTIVECONTENT
Parameter Name:	PDF_LAUNCH
Parameter Type:	Bool
Description:	Identify "/Launch" as active content
Default:	1
Set via:	Configuration files

Section Name:ACTIVECONTENTParameter Name:PDF_ACROFORMParameter Type:BoolDescription:identify "/AcroForm" as active contentDefault:1Set via:Configuration files

Section Name:ACTIVECONTENTParameter Name:PDF_RICHMEDIAParameter Type:BoolDescription:identify "/RichMedia" as active contentDefault:1Set via:Configuration files

Section Name: ACTIVECONTENT

Parameter Name:MSOFFICE_MACROParameter Type:BoolDescription:identify macros in MS Office files (POLE and OOXML) as active contentDefault:1Set via:Configuration files

Section Name:ACTIVECONTENTParameter Name:MSOFFICE_JAVAParameter Type:BoolDescription:identify JavaClasses in MS Office OOXML filesDefault:1Set via:Configuration files

Section Name:ACTIVECONTENTParameter Name:MSOFFICE_OLEParameter Type:BoolDescription:identify OLE embedded objects as active content (no recursive scan)Default:1Set via:Configuration files

Section Name:	ACTIVECONTENT
Parameter Name:	ZIP_JAVAARCHIVE
Parameter Type:	Bool
Description:	identify ZIP Archives containing Java Archive artefacts (JAR) as
	active content
Default:	1
Set via:	Configuration files
Section Name:	ACTIVECONTENT
Parameter Name	HTML SCRIPT
Parameter Type:	Bool
Description:	identify HTML as active content when containing:
Description.	
	- InvaScript
Default	1
Delault.	Configuration files
Set via.	Configuration mes
Section Name:	ACTIVECONTENT
Parameter Name:	HTML_EVENTHANDLER
Parameter Type:	Bool
Description:	identify HTML containing event handler registrations as active
	content
Default:	1
Set via:	Configuration files
Section Name:	ACTIVECONTENT
Parameter Name:	GIFAR
Parameter Type:	Bool
Description:	identify chameleon files (i.e. GIFAR) as active content
Default:	1
Set via:	Configuration files

Section Name:ACTIVECONTENTParameter Name:FLASHParameter Type:BoolDescription:identify Macromedia Flash as active contentDefault:1Set via:Configuration files

Section Name:ACTIVECONTENTParameter Name:SILVERLIGHTParameter Type:BoolDescription:identify Microsoft Silverlight as active contentDefault:1Set via:Configuration files

Section Name: ACTIVECONTENT

Parameter Name:EXECUTABLEParameter Type:BoolDescription:identify all executable file types as active contentDefault:1Set via:Configuration files.

Section Name:ACTIVECONTENTParameter Name:XML_JAVASCRIPTParameter Type:BoolDescription:identify JavasScript in XML as active contentDefault:1Set via:Configuration files.

Quarantine Parameters

Section Name:	QUARANTINE
Parameter Name:	ON_BLOCK
Parameter Type:	Bool
Description:	Copy files blocked to en encrypted quarantine file
Default:	0
Set via:	Configuration files.

Section Name:	QUARANTINE
Parameter Name:	ON_ERROR
Parameter Type:	Bool
Description:	Copy to en encrypted quarantine file if a scan error occurred
Default:	0
Set via:	Configuration files.

Section Name: QUARANTINE

Parameter Name:QUARANTINEPATHParameter Type:CharDescription:Directory where encrypted quarantine files should be storedDefault:n/aSet via:Configuration files.

Section Name:	QUARANTINE
Parameter Name:	QUARANTINEPASSWORD
Parameter Type:	Char
Description:	Password/Key for the encryption of the quarantined files
Default:	n/a
Set via:	Configuration files.

Update Parameter

Section Name:	UPDATE
Parameter Name:	SERVER
Parameter Type:	Char
Description:	IP-Address or host name of an alternative update source (LUS)
Default:	n/a
Set via:	Configuration files

Section Name:	UPDATE
Parameter Name:	PROXY
Parameter Type:	Char
Description:	configuration of an \ensuremath{HTTP} proxy to be used for downloading the updates.
	Syntax:
	<proxyname ip="">:<proxyport></proxyport></proxyname>
	or
	<username>:<password>@<proxyname ip="">:<proxyport></proxyport></proxyname></password></username>
Default:	n/a
Set via:	Configuration files

Section Name:	UPDATE	
Parameter Name:	POLL_INTERVAL	
Parameter Type:	Integer	
Description:	Number of seconds before querying the update source for a new signature	file
Default:	300 (5min)	
Set via:	Configuration file	

Section Name:	UPDATE
Parameter Name:	POLL_TURNAROUND
Parameter Type:	Integer
Description:	Specifies after how many patter update queries an engine update query is to be performed
Default:	288 (24 hrs for the default POLL_INTERVAL of 300s)
Set via:	Configuration files

Section Name:	UPDATE
Parameter Name:	AUTHENTICATE
Parameter Type:	Bool
Description:	Specifies whether the update requests should be authenticated with the license signature
Default:	1
Set via:	Configuration files

Section Name:	UPDATE
Parameter Name:	PATTERN_WARN_AGE
Parameter Type:	Integer
Description:	Specifies the age (in days) of the virus signature file after which the ON_PATTERNTOOOLD event will be generated to
	notify the admin of potentially outdated signatures
Default:	5
Set via:	Configuration files

Section Name:	UPDATE	
Parameter Name:	PATTERN_BLOCK_AGE	
Parameter Type:	Integer	
Description:	Specifies the age (in days) of the virus signature files after which all scans	will be blocked with "Virus signature too old"
Default:	30	
Set via:	Configuration files	

Section Name:	UPDATE
Parameter Name:	GET_SCANENGINE
Parameter Type:	Bool
Description:	Toggles whether automatic download and installation of the scan engine component should be performed.
Default:	1
Set via:	Configuration files

Section Name:	UPDATE
Parameter Name:	GET_VIRUSDATA
Parameter Type:	Bool
Description:	Toggles whether automatic download and installation of the virus definitions should be performed.
Default:	1
Set via:	Configuration files

Section Name:	UPDATE
Parameter Name:	VSE_ENGINEDIR
Parameter Type:	Char
Description:	Directory of the McAfee virus scan engine to monitor for changes. If set, no updates will be downloaded from the
	bowbridge CDN
Default:	n/a
Set via:	Configuration files

Section Name:	UPDATE
Parameter Name:	VSE_DATDIR
Parameter Type:	Char
Description:	Directory of the McAfee virus definition files to monitor for changes
Default:	n/a
Set via:	Configuration files

Section Name:	UPDATE
Parameter Name:	EXTRADATDIR
Parameter Type:	Char
Description:	Directory of the McAfee extra virus definition files to monitor for changes
Default:	n/a
Set via:	Configuration files

Custom notification parameters

These parameters map internal notification events to OS-level scripts in the custom_alerts subfolder. The scripts are executed upon each of these events.

Section Name: SCRIPTS Parameter Name: ON_STARTUP Script input Engine name and version

Section Name: SCRIPTS Parameter Name: ON_SHUTDOWN Script input: n/a

Section Name: SCRIPTS Parameter Name: ON_FILE_BLOCKED Script input: filename, blocking reason

Section Name: SCRIPTS Parameter Name: ON_STARTUP_ERROR Script input: failure reason

Section Name: SCRIPTS Parameter Name: ON_SCAN_ERROR Script input: filename, error description

Section Name:SCRIPTSParameter Name:ON_UPDATEScript input:component updated (engine/signature)

Section Name:SCRIPTSParameter Name:ON_UPDATE_ERRORScript input:component failed to update (engine/signature)



Section Name:SCRIPTSParameter Name:ON_PATTERNTOOOLDScript input:descriptive message

Miscellaneous parameters:

Section Name:	EPO
Parameter Name:	EPOLOG
Parameter Type:	Bool
Description:	Toggles the generation of log and event information for the McAfee ePO integration
Default:	0
Set via:	Configuration files

Section Name:	MISC
Parameter Name:	LEGACY_MODE
Parameter Type:	Bool
Description:	Switches the adapter to legacy mode. In this mode, the VSA only advertises VSI 1.0 functionality to the SAP processes
	for backward compatibility. In legacy mode several features for which there are not SAP SAP Customizing
	switches can be set through the configuration file only.
Default:	0
Set via:	Configuration files



bowbridge Software GmbH Altrottstraße 31 **~** 69190 Walldorf **~** Germany

- **t** +49-6227-69899-50
- e sales@bowbridge.net
- www.bowbridge.net

bowbridge Software USA

530 Lytton Ave, 2nd Floor
Palo Alto, CA 94301
United States

- **t** +1-650-617-3408
- e us-sales@bowbridge.net
- www.bowbridge.net

b~wbridge